

## [Jan-2019] 100% Real 300-365 PDF Dumps 138Q Free Download in Braindump2go(Q96-Q106)

**2019/Jan Braindump2go 300-365 Exam Dumps with PDF and VCE New Updated Today! Following are some new 300-365 Real Exam Questions:]**1.**2019 Latest 300-365 Exam Dumps (VCE & PDF) Instant Download:**

**<https://www.braindump2go.com/300-365.html>**2.**2019 Latest 300-365 Exam Questions & Answers Download:**

**<https://drive.google.com/drive/folders/0B75b5xYLjSSNZTJ3Y0Z5b0NFRFE?usp=sharing>** QUESTION 96 What is the AQ sensitivity when the EDRRM is set to high? A. 60 B. 35 C. 40 D. 50 Answer: A Explanation: The EDRRM AQ threshold value for low sensitivity is 35, medium sensitivity is 50, and high sensitivity is 60. QUESTION 97 How many mDNS profiles can you apply per WLAN? A. 2 B. 3 C. 4 D. 1 Answer: D Explanation: Note Only one mDNS profile can be applied to one WLAN QUESTION 98 Clients at a remote FlexConnect site with ID 338789750 are experiencing poor roaming despite the fact that Cisco Centralized Key Management is enabled on the SSID. Which FlexConnect feature must be configured to resolve this issue? A. local authentication B. central switching C. learn client IP address D. FlexConnect group Answer: D QUESTION 99 An engineer must create data-link redundancy for the company Cisco Wireless LAN Controller. The engineer has decided to configure LAG-based redundancy instead of port-based redundancy. Which three features of LAG-based redundancy helped steer this decision? (Choose three.) A. All interface traffic passes as long as one port is up. B. Multiple untagged dynamic interfaces on same port. C. Interface connection to two separate non-stacked switches. D. Packets are always sent out on the same port they are received on. E. Full bandwidth of all links available. F. Ports are grouped into multiple LAGs. Answer: ADF QUESTION 100 A network engineer just finished deploying a converged access wireless infrastructure. The configuration consists of Cisco Catalyst 3850 Series switches operating as mobility controllers and agents in multiple switch peer groups and mobility subdomains. Which change must be made to allow for seamless roaming between switch peer groups? A. Add one Cisco 5760 WLC as a mobility oracle and configure on each of the mobility controllers in the converged access infrastructure. B. Add another Cisco Catalyst 3850 switch as a mobility oracle and configure on each of the mobility controllers in the converged access infrastructure. C. Convert one controller to a mobility oracle while the other mobility controllers and agents should be configured in the same mobility domain. D. Configure all switches as mobility controllers in the same switch peer group to allow for seamless roaming. Answer: D QUESTION 101 You have VoWiFi running on FlexConnect AP with centrally-switched SSID. Which configuration must be performed to preserve marking for central-switching SSID? A. Trust DSCP B. This will not work. The WLAN should be locally switched and we need to trust CoS. C. Trust CoS D. No need to trust anything. It should work fine because the WLAN is centrally switched. Answer: A QUESTION 102 An engineer is attempting to send multicast data to all multicast routers in the network with ID 338789750. Which IP address should be used? A. 224.0.0.1 B. 224.0.0.2 C. 224.0.0.4 D. 224.0.0.3 Answer: B QUESTION 103 An engineer is configuring visitor connect on their Cisco MSE. Which URL must they use for their redirection URL? A. <http://<mse>:8083/visitor/login.do> B. <http://<mse>:8084/fbwifi/forward> C. <http://<mse>:8083/fbwifi/forward> D. <http://<mse>:8084/visitor/login.do> Answer: A Explanation:

**[https://www.cisco.com/c/en/us/td/docs/wireless/mse/8-0/CMX\\_Connect\\_Engage\\_Visitor\\_Connect/Guide/Cisco\\_CMX\\_Connect\\_Engage\\_Config\\_Guide\\_VC/CMX\\_Dashboard\\_Visitor\\_Connect.html](https://www.cisco.com/c/en/us/td/docs/wireless/mse/8-0/CMX_Connect_Engage_Visitor_Connect/Guide/Cisco_CMX_Connect_Engage_Config_Guide_VC/CMX_Dashboard_Visitor_Connect.html)** QUESTION 104 An engineer wants to identify historical data collected by the Cisco MSE on rogue access points over the past two years. If the Cisco MSE is configured for maximum historical data retention, how many months can be searched? A. 24 B. 36 C. 6 D. 12 Answer: D QUESTION 105 A wireless engineer must optimize RF performance for multiple buildings with multiple types of construction and user density. Which two actions must be taken? (Choose two.) A. Enable DTTPC on the network. B. Configure RF Profiles for each area type. C. Configure WMM profiles for each building. D. Configure FlexConnect groups for each building. E. Configure AP groups for each area type. Answer: BE QUESTION 106 A customer has configured a wireless LAN controller and set the 802.11a/n data rates. All rates are enabled where 5.5 Mbps, 11 Mbps, and 24 Mbps are set to Mandatory. What will APs send over the 24 Mbps data rate? A. channel announcements B. DTTPC support C. multicast broadcast D. beacons Answer: C !!!RECOMMEND!!! 1.**2019 Latest 300-365 Exam Dumps (VCE & PDF) Instant Download:****<https://www.braindump2go.com/300-365.html>**2.**2019 Latest 300-365 Study Guide Video:** YouTube Video: [YouTube.com/watch?v=IAyellszH4I](https://www.youtube.com/watch?v=IAyellszH4I)