

## [June-2019-New640-878 140Q PDF and VCE Files Free Offered By Braindump2go

2019 Latest Braindump2go CCNA Service Provider 640-878 SPNGN2 Dumps with PDF and VCE New Updated Today! Following are some new 640-878 Exam Questions:1. |2019 Latest 640-878 Exam Dumps (PDF & VCE) Instant

Download:<https://www.braindump2go.com/640-878.html>2. |2019 Latest 640-878 Exam Questions & Answers Instant

Download:<https://drive.google.com/drive/folders/0B75b5xYLjSSNVm1SMFBqbjlzbEU?usp=sharing>New QuestionWhich number range is allocated to private Autonomous Systems by the Internet Assigned Numbers Authority?A. 65535 to 65545B. 64535 to 64536C. 64512 to 65535D. 65535 to 66001E. 63512 to 64535**Answer: C**

New QuestionWhich of the following commands would be used to prevent a switchport from processing Bridge Protocol Data Units?A. switch(config)#bpdu filter enableB. switch(config)#no bpdu enableC. switch(config-if)#spanning-tree bpdufilter enableD. switch(config-if)#no spanning-tree bpdu filter enableE. switch(config-if)#spanning-tree bpdu guard**Answer: C**

New QuestionWhich commands will configure the spanning tree operating mode that can group multiple VLANs in a single domain?A. switch(config)#spanning-tree mode pvstB. switch(config)#spanning-tree mode rstpC. switch(config)#spanning-tree mode rapid-pvstD. switch(config)#spanning-tree mode mstE. switch(config)#spanning-tree mode mst-plus**Answer: D**

New QuestionA customer has created a new VLAN for the subnet that was allocated to them. Computers on the subnets can ping their default gateway, but they cannot ping devices in the other subnet. What is most likely the problem?A. Firewall on the Provider Edge is blocking accessB. InterVLAN routing is not configuredC. BGP has not been configured with the Provider Edge routerD. VLAN Switched Virtual Interface is in a down state**Answer: B**

New QuestionWhich command configures a switchport to connect only a host device in VLAN 301?A. switchport access vlan 301B. switchport mode trunk vlan 301C. switchport mode access vlan 301D. switchport vlan 301**Answer: A**

New QuestionWhich two commands are required to configure an access port for both voice VLAN 20 and data VLAN 30? (Choose two.)A. switchport mode access 30B. switchport data vlan 30C. switchport access data 20D. switchport access data 30E. switchport access vlan 30F. switchport mode voice 20G. switchport voice vlan 20**Answer: EG**

New QuestionRefer to the exhibit. Which three commands are required on interface fastethernet 5/6 in order to create a trunk link between another Cisco Catalyst Switch? (Choose three.) A. no shutdownB. switchport mode trunkC. encapsulation trunkD. switchport trunk encapsulation dot1QE. switchport trunk enableF. no switchportG. interface fastethernet 5/6 trunkH. switchport trunk allow dot1Q**Answer: ABD**

New QuestionA customer has been allocated a new VLAN on a new Layer 3 switch. After configuring the Switched Virtual Interface, what additional two configurations are required to ensure the switch can route packets to the Internet through a gateway with IP address of 209.165.200.250? (Choose two.)A. IP default-gateway 209.165.200.250B. IP routingC. IP route 0.0.0.0 0.0.0.0 209.165.200.250D. IP routing 0.0.0.0 0.0.0.0 209.165.200.250E. IP networking**Answer: BC**

New QuestionRefer to the partial Cisco IOS-XR configuration. What is the purpose of the for PFX to PEER command?!mpls ldplabel advertisedisablefor PFX to PEER!  
<output omitted>!A. To selectively enable LDP peering(s) with specific neighborsB. To selectively disable LDP peering(s) with specific neighborsC. To perform outbound filtering for local label advertisement for one or more prefixes to one or more peersD. To perform inbound filtering for local label advertisement for one or more prefixes from one or more peers**Answer: C**

New QuestionWhat does the command 'rep admin vlan 100' accomplish?A. confines flooding of REP messages to VLAN 100B. reserves REP admin VLAN to 100 so that no REP messages are sent on VLAN 100C. forces VLAN 100 into a REP block stateD. this is an invalid command**Answer: A**

New QuestionAfter configuring Q-in-Q on a new interface, the customer has requested that the IOS version and remote model also be viewable via the trunk. What additional command would need to be applied to both sides of the Q-in-Q trunk?A. l2protocol-tunnel cdpB. l2protocol-tunnel stpC. l2protocol-tunnel vtp D. l2protocol-tunnel lldpE. l2protocol-tunnel odr**Answer: A**!!!RECOMMEND!!!

1. |2019 Latest 640-878 Exam Dumps (PDF & VCE) Instant Download:<https://www.braindump2go.com/640-878.html>2. |2019 Latest 640-878 Study Guide Video Instant Download: YouTube Video: [YouTube.com/watch?v=8j0vVPMpcCk](https://www.youtube.com/watch?v=8j0vVPMpcCk)